NSN 5305-01-285-4915

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-285-4915 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.360 inches and 0.390 inches **Fastener Length:** Between 0.735 inches and 0.765 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.438 inches and 0.453 inches **Head Height:** Between 0.240 inches and 0.260 inches **First Diameter From Head:** Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.365 inches and 0.385 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Astm a380 assn standard single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-285-4915

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0