## NSN 5305-01-285-5980



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-285-5980 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.820 inches and 0.880 inches **Fastener Length:** Between 2.830 inches and 2.870 inches **Head Style:** Flat chamfer **Head Diameter:** Between 1.287 inches and 1.312 inches **Head Height:** Between 0.610 inches and 0.635 inches **Shoulder Diameter:** 0.996 inches first shoulder and 0.998 inches first shoulder **Shoulder Length:** 1.990 inches first shoulder and 2.010 inches first shoulder Single Shear Strength: 25000 pounds per square inch **Internal Drive Style:** Hexagon **Thread Diameter:** 0.750 inches Width Across Flats: Between 0.503 inches and 0.510 inches Thready Qty Per Inch (tpi): 10 **Shoulder Shape:** Round first shoulder **Special Features:** Plain or knurl head; neck between shoulder and threads 0.150 lg.; 0.605-0.638 dia Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** 

Qq-p-416 type 2 cl 3 federal specification single treatment response

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

## NSN 5305-01-285-5980

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0