NSN 5305-01-285-6923

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-285-6923 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.120 inches **Fastener Length:** 0.440 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** 0.112 inches **First Diameter From Head:** Between 0.073 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.290 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: 0.0937 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Threaded neck 0.020-0.030 in. Lg; 0.112 in. Dia Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment:** Passivate **Surface Treatment Specification:** Qq-p-35 type 4 federal specification single treatment response

Unc

Thread Series Designator:

NSN 5305-01-285-6923

Externally Relieved Body Screw - Page 2 of 2



| | Life: |
|--|-------|
| | |
| | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0