

NSN 5305-01-285-7719 Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-285-7719 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.387 inches and 0.500 inches **Fastener Length:** Between 0.470 inches and 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.550 inches and 0.562 inches **Head Height:** Between 0.368 inches and 0.375 inches **Hole Diameter:** Between 0.061 inches and 0.067 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: Between 0.3125 inches and 0.3160 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Hole Configuration Style:** Round internal hexagon

Material:

Iron alloy 660

**Material Specification:** 

Ams 5737 assn standard single material response

**Surface Treatment:** 

**Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unrf

## NSN 5305-01-285-7719

Socket Head Cap Screw - Page 2 of 2



Sı	pe	cifi	cati	on	Data:
•	$\sim$	•••	outi	•••	Dutu.

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0