

View Online at <https://aerobasegroup.com/nsn/5305-01-285-7725>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.380 inches and 0.447 inches

**Fastener Length:**

Between 0.890 inches and 0.937 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.3765 inches and 0.3813 inches

**Head Height:**

Between 0.032 inches and 0.034 inches

**Shoulder Diameter:**

0.2177 inches first shoulder and 0.2182 inches first shoulder

**Shoulder Length:**

0.490 inches first shoulder and 0.510 inches first shoulder

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.190 inches

**Features Provided:**

Dry film lubricant and o ring

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

1250000 pounds per square inch

**Countersink Angle:**

100.0 degrees

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 federal specification single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0