

View Online at <https://aerobasegroup.com/nsn/5305-01-285-9970>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.838 inches and 2.000 inches

Fastener Length:

Between 1.938 inches and 2.000 inches

Head Style:

Pan

Head Diameter:

Between 0.473 inches and 0.492 inches

Head Height:

Between 0.162 inches and 0.175 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

60000 pounds per square inch

Screw Material:

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025 or steel comp 1026 or steel comp 1029 or steel comp 1030 or steel comp 1031 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040

Screw Material Specification:

66 federal standard all material responses

Screw Surface Treatment:

Zinc

Screw Surface Treatment Specification:

Astm b633 assn standard single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

3 type and 9 style

Departure From Cited Document:

As modified by surface treatment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0