## NSN 5305-01-285-9975

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-285-9975

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.315 inches
Fastener Length:
Between 1.440 inches and 1.500 inches
Head Style:
Flat chamfer
Head Diameter:
Between 1.107 inches and 1.125 inches
Head Height:
Between 0.740 inches and 0.750 inches
Locking Feature:
Patch threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.750 inches
Width Across Flats:
Between 0.625 inches and 0.631 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
170000 pounds per square inch
Hardness Rating:
37.0 rockwell c fastener and 45.0 rockwell c fastener
Minimum Yield Strength:
150000 pounds per square inch
Material:
Steel fastener
Surface Treatment:
Cadmium fastener and chromate fastener
Surface Treatment Specification:
Qq-p-416, type 2 class 2 federal specification single treatment response fastener
Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:

N/a

## NSN 5305-01-285-9975

Socket Head Cap Screw - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A003b0