## NSN 5305-01-286-0867

N/a

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-286-0867

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.208 inches and 0.258 inches
Fastener Length:
Between 0.280 inches and 0.310 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.194 inches and 0.225 inches
Locking Feature:
Strip threads or pellet threads or patch threads
Internal Drive Style:
High-torque
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
39.0 rockwell c fastener and 43.0 rockwell c fastener
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Plastic polyamide locking feature
Material Specification:
Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener
Thread Series Designator:
Unjc
Specification Data:
80205-nas1221 professional/industrial association standard
Shelf Life:

## NSN 5305-01-286-0867

Socket Head Cap Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0