NSN 5305-01-286-3095

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-286-3095 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.808 inches and 0.875 inches **Fastener Length:** Between 0.844 inches and 0.875 inches **Head Style:** Pan **Head Diameter:** Between 0.136 inches and 0.140 inches **Head Height:** Between 0.044 inches and 0.053 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 39.0 rockwell c and 43.0 rockwell c **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5737 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1101 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-286-3095

Machine Screw - Page 2 of 2



Fiig:

A500d0