NSN 5305-01-286-3100

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-286-3100

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.559 inches and 0.625 inches
Fastener Length:
Between 0.595 inches and 0.625 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.134 inches and 0.140 inches
Head Height:
Between 0.083 inches and 0.086 inches
Locking Feature:
Strip threads or patch threads or pellet threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.086 inches
Width Across Flats:
Between 0.078 inches and 0.079 inches
Thready Qty Per Inch (tpi):
56
Min. Tensile Strength (psi):
155000 pounds per square inch
Hardness Rating:
38.0 rockwell c fastener and 45.0 rockwell c fastener
Product Name:
Navy special project
Material:
Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp xm-7 fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener
Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-01-286-3100

Socket Head Cap Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0