

View Online at <https://aerobasegroup.com/nsn/5305-01-286-3100>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.559 inches and 0.625 inches

**Fastener Length:**

Between 0.595 inches and 0.625 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.134 inches and 0.140 inches

**Head Height:**

Between 0.083 inches and 0.086 inches

**Locking Feature:**

Strip threads or patch threads or pellet threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.086 inches

**Width Across Flats:**

Between 0.078 inches and 0.079 inches

**Thread Qty Per Inch (tpi):**

56

**Min. Tensile Strength (psi):**

155000 pounds per square inch

**Hardness Rating:**

38.0 rockwell c fastener and 45.0 rockwell c fastener

**Product Name:**

Navy special project

**Material:**

Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp xm-7 fastener

**Surface Treatment:**

Passivate fastener

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response fastener

**Thread Series Designator:**

Unrc

**Specification Data:**

80205-nas1352 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0