## NSN 5305-01-286-3112

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-286-3112 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.219 inches and 0.357 inches **Fastener Length:** Between 1.163 inches and 1.297 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.297 inches and 0.302 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.940 inches and 0.944 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 95000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-286-3112

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0