## NSN 5305-01-286-3504

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-286-3504 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.125 inches and 1.438 inches **Fastener Length:** Between 1.398 inches and 1.438 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.457 inches and 0.469 inches **Head Height:** Between 0.306 inches and 0.312 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 80.0 rockwell b fastener Material: Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 306 fastener or steel comp 316 fasten steel comp xm-7 fastener **Surface Treatment:** Passivate fastener **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response fastener **Thread Series Designator:** Unrc **Specification Data:** 80205-nas1352 professional/industrial association standard

--

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5305-01-286-3504

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0