Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-286-5431

view Online at https://defobd3egioup.com/h3h/3003-01-200-343	
Thread Class:	
3a Thread Direction:	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.670 inches and 0.750 inches	
Fastener Length:	
Between 0.720 inches and 0.750 inches	
Head Style: Flat chamfer	
Head Diameter:	
Between 0.176 inches and 0.183 inches	
Head Height:	
Between 0.108 inches and 0.112 inches	
Locking Feature:	
Patch threads or pellet threads or strip threads	
Internal Drive Style:	
Thread Diameter:	
0.112 inches	
Width Across Flats:	
Between 0.0937 inches and 0.0957 inches	
Thready Qty Per Inch (tpi):	
Min. Tensile Strength (psi):	
160000 pounds per square inch	
Material:	
Plastic polyamide locking feature	
Material Specification:	
Ams 5731 assn standard single material response fastener or an	is 5737 assn standard single material response fastener
Surface Treatment:	
Passivate fastener	
Surface Treatment Specification:	
Qq-p-35 federal specification single treatment response fastener	
Thread Series Designator:	
Unrc	
Specification Data:	
80205-nas1352 professional/industrial association standard	
Shelf Life:	
N/a	
Unit Of Measure:	
-	

NSN 5305-01-286-5431

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

