

View Online at <https://aerobasegroup.com/nsn/5305-01-286-5431>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.670 inches and 0.750 inches

**Fastener Length:**

Between 0.720 inches and 0.750 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.176 inches and 0.183 inches

**Head Height:**

Between 0.108 inches and 0.112 inches

**Locking Feature:**

Patch threads or pellet threads or strip threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.112 inches

**Width Across Flats:**

Between 0.0937 inches and 0.0957 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Material:**

Plastic polyamide locking feature

**Material Specification:**

Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener

**Surface Treatment:**

Passivate fastener

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response fastener

**Thread Series Designator:**

Unrc

**Specification Data:**

80205-nas1352 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0