## NSN 5305-01-286-5436

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-286-5436 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.477 inches and 0.636 inches **Fastener Length:** Between 1.467 inches and 1.487 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.360 inches and 0.404 inches Single Shear Strength: 1700 pounds per square inch **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: 0.156 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches grip **Special Features:** 0.112 in. Dia. Hole for ca2105 cagec 29372 plug; 040 in. Wide x 0.029 in. Deep splines 120 degrees apart Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf

N/a

Shelf Life:

## NSN 5305-01-286-5436

Socket Head Cap Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0