

View Online at <https://aerobasegroup.com/nsn/5305-01-286-5436>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.477 inches and 0.636 inches

Fastener Length:

Between 1.467 inches and 1.487 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.360 inches and 0.404 inches

Single Shear Strength:

1700 pounds per square inch

Internal Drive Style:

Hexagon

Thread Diameter:

0.250 inches

Width Across Flats:

0.156 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches grip

Special Features:

0.112 in. Dia. Hole for ca2105 cagec 29372 plug; 040 in. Wide x 0.029 in. Deep splines 120 degrees apart

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0