Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-286-6026

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.360 inches and 0.390 inches
Fastener Length:
Between 0.860 inches and 0.890 inches
Head Style:
Knurled no. 4
Head Diameter:
Between 0.438 inches and 0.453 inches
Head Height:
Between 0.240 inches and 0.260 inches
First Diameter From Head:
Between 0.125 inches and 0.135 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.490 inches and 0.510 inches
Point Style:
Cone
Internal Drive Style:
Slot
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 303
Material Specification:
Astm a582 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Astm a380 assn standard single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0