3a

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-286-7979



## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 3.016 inches and 3.250 inches Fastener Length: Between 3.170 inches and 3.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.735 inches and 0.750 inches **Head Height:** Between 0.492 inches and 0.500 inches Locking Feature: Patch threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: Between 0.3750 inches and 0.3790 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c fastener and 45.0 rockwell c fastener **Minimum Yield Strength:** 155000 pounds per square inch Material: Steel fastener Surface Treatment: Cadmium fastener and chromate fastener Surface Treatment Specification: Qq-p-416 ty2 cl3 federal specification single treatment response fastener **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure:

---

13

## NSN 5305-01-286-7979

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

