NSN 5305-01-286-7980

N/a

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-286-7980

Thread Class.
Thread Class:
3a Through Birnerian
Thread Direction:
Right-hand Thread Longth;
Thread Length:
1.500 inches
Fastener Length:
Between 1.940 inches and 2.000 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.735 inches and 0.750 inches
Head Height:
Between 0.492 inches and 0.500 inches
Locking Feature:
Strip threads or pellet threads or patch threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.500 inches
Width Across Flats:
Between 0.375 inches and 0.379 inches
Thready Qty Per Inch (tpi):
13
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
33.0 rockwell c fastener and 42.0 rockwell c fastener
Material:
Plastic polyamide locking feature
Material Specification:
Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener
Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:

NSN 5305-01-286-7980

Socket Head Cap Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0