NSN 5305-01-287-3569

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-287-3569 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.279 inches and 0.380 inches **Fastener Length:** Between 0.350 inches and 0.380 inches **Head Style:** Pan **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 62000 pounds per square inch **Screw Material:** Aluminum alloy 2024 **Screw Material Specification:** Qq-a-200/3 federal specification single material response or qq-a-225/6 assn standard single material response **Screw Surface Treatment:** Anodize **Screw Surface Treatment Specification:** Mil-a-8625 type 1, type 2 class 1 military specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 3 type and 9c style Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A500d0

NSN 5305-01-287-3569

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.