NSN 5305-01-287-5771

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-287-5771 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.334 inches and 0.369 inches **Fastener Length:** Between 0.584 inches and 0.614 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.490 inches and 0.510 inches **Head Height:** Between 0.146 inches and 0.166 inches **First Diameter From Head:** Between 0.245 inches and 0.248 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.245 inches and 0.250 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Aisi assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-287-5771

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0