

View Online at <https://aerobasegroup.com/nsn/5305-01-287-5777>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

2.286 inches

Fastener Length:

Between 2.440 inches and 2.500 inches

Head Style:

Square

Head Height:

Between 0.361 inches and 0.369 inches

Width Between Flats:

Between 0.484 inches and 0.500 inches

Point Style:

Cup

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.500 inches

Thready Qty Per Inch (tpi):

13

Hardness Rating:

30.0 rockwell c and 37.0 rockwell c

Product Name:

Setscrew

Material:

Steel comp 1010 or steel comp 1011 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1035 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1042 or steel comp 1043 or steel comp 1044 or steel comp 1045 or steel comp 1212 or steel comp 1213 or steel comp 1137 or steel comp 1139 or steel comp 1140 or steel comp 1141 or steel comp 1144

Material Specification:

66 federal standard all material responses

Surface Treatment:

Zinc

Surface Treatment Specification:

Astm b633 assn standard single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

1 type and 4 style

Departure From Cited Document:

Modified by surface treatment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0