## NSN 5305-01-287-5777

Setscrew - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5305-01-287-5777   |
|---|
| Thread Class:   |
| 2a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 2.286 inches  |
| Fastener Length:  |
| Between 2.440 inches and 2.500 inches   |
| Head Style:   |
| Square  |
| Head Height:  |
| Between 0.361 inches and 0.369 inches   |
| Width Between Flats:  |
| Between 0.484 inches and 0.500 inches   |
| Point Style:  |
| Cup   |
| Internal Drive Style:   |
| W/o internal drive  |
| Thread Diameter:  |
| 0.500 inches  |
| Thready Qty Per Inch (tpi):   |
| 13  |
| Hardness Rating:  |
| 30.0 rockwell c and 37.0 rockwell c   |
| Product Name:   |
| Setscrew  |
| Material:   |
| Steel comp 1010 or steel comp 1011 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 |
| or steel comp 1019 or steel comp 1020 or steel comp 1035 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp   |
| 1040 or steel comp 1042 or steel comp 1043 or steel comp 1044 or steel comp 1045 or steel comp 1212 or steel comp 1213 or steel   |
| comp 1137 or steel comp 1139 or steel comp 1140 or steel comp 1141 or steel comp 1144   |
| Material Specification:   |
| 66 federal standard all material responses  |
| Surface Treatment:  |
| Zinc  |
| Surface Treatment Specification:  |
| Astm b633 assn standard single treatment response   |
| Thread Series Designator:   |
| Unc   |
| Specification Or Standard:  |
| 1 type and 4 style  |
| Departure From Cited Document:  |

N/a

Shelf Life:

Modified by surface treatment

## NSN 5305-01-287-5777

Setscrew - Page 2 of 2



|  |  |  | ire: |  |
|--|--|--|------|--|

--

Demilitarization:

No

Fiig:

A003b0