NSN 5305-01-287-6288

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-287-6288

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.313 inches and 0.363 inches
Fastener Length:
Between 0.448 inches and 0.478 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.328 inches and 0.385 inches
Grip Diameter:
Between 0.1881 inches and 0.1887 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Grip Length:
Between 0.115 inches and 0.135 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
180000 pounds per square inch
180000 pounds per square inch Countersink Angle:
Countersink Angle:
Countersink Angle: Between 99.0 degrees and 101.0 degrees
Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish:
Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head
Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head Material:
Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head Material: Iron alloy 660
Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head Material: Iron alloy 660 Material Specification:
Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment:
Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate
Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf
Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data:
Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf

N/a

NSN 5305-01-287-6288

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0