

View Online at <https://aerobasegroup.com/nsn/5305-01-288-7832>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.325 inches and 0.375 inches

**Fastener Length:**

0.375 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.166 inches and 0.183 inches

**Head Height:**

Between 0.072 inches and 0.079 inches

**Hole Diameter:**

0.039 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.112 inches

**Hole Quantity:**

1

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

55000 pounds per square inch

**Screw Material:**

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1031 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1040 or steel comp 1541

**Screw Material Specification:**

Aisi assn standard single material response

**Screw Surface Treatment:**

Zinc and chromate

**Screw Surface Treatment Specification:**

Astm a633 type 2 cl fe/zn 13 assn standard single treatment response

**Head Hole Configuration Style:**

Round

**Thread Series Designator:**

Unc

**Specification Or Standard:**

1 type and 5s style

**Departure From Cited Designator:**

As modified by surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0