NSN 5305-01-288-9353

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-288-9353 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.169 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches **Spline Minor Diameter:** Between 0.096 inches and 0.098 inches **Spline Major Diameter:** Between 0.113 inches and 0.115 inches **Spline Width:** Between 0.023 inches and 0.025 inches **Internal Drive Style:** Six spline **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 125000 pounds per square inch Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 385 **Material Specification:** Qq-s-763 federal specification all material responses **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5305-01-288-9353

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0