## NSN 5305-01-288-9544

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-288-9544

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 1.140 inches   |
| Fastener Length:   |
| 1.140 inches   |
| Head Style:  |
| Pan no. 2  |
| Head Diameter:   |
| 0.374 inches   |
| Head Height:   |
| 0.125 inches   |
| Hole Diameter:   |
| 0.045 inches   |
| Internal Drive Style:                                      |
| High-torque  |
| Thread Diameter:   |
| 0.190 inches   |
| Hole Quantity:   |
| 1  |
| Thready Qty Per Inch (tpi):                                |
| 32   |
| Min. Tensile Strength (psi):                               |
| 160000 pounds per square inch                              |
| Screw Material:  |
| Stainless steel  |
| Screw Surface Treatment:                                   |
| Passivate  |
| Screw Surface Treatment Specification:                     |
| Qq-p-35 federal specification single treatment response    |
| Head Hole Configuration Style:                             |
| Round  |
| Thread Series Designator:                                  |
| Unjf   |
| Specification Data:  |
| 80205-nas1216 professional/industrial association standard |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 5305-01-288-9544

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0