NSN 5305-01-289-5852

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-289-5852 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.375 inches and 0.390 inches **Fastener Length:** Between 1.235 inches and 1.280 inches **Head Style:** Round extended washer **Head Height:** Between 0.105 inches and 0.115 inches **Extended Washer Diameter:** Between 0.365 inches and 0.385 inches **First Diameter From Head:** Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.860 inches and 0.890 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** O-ring under head Material: Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener **Material Specification:** Qq-s-763 federal specification all material responses fastener **Surface Treatment:** Passivate fastener **Surface Treatment Specification:** Mil-s-5002 military specification single treatment response fastener **Thread Series Designator:** Unc Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-289-5852

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.