## NSN 5305-01-289-5854

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-289-5854 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.670 inches and 0.701 inches **Fastener Length:** Between 0.781 inches and 0.812 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.456 inches and 0.506 inches **Internal Drive Style:** Tri-wing recess **Thread Diameter:** 0.2500 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification 1st treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas5604 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Mil-s-5000 spec.

Mil-std (military Standard):

Fiig: A500d0