

View Online at <https://aerobasegroup.com/nsn/5305-01-289-6158>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.178 inches and 0.198 inches

Fastener Length:

Between 0.422 inches and 0.454 inches

Head Style:

Fillister

Head Diameter:

Between 0.250 inches and 0.270 inches

Head Height:

Between 0.102 inches and 0.113 inches

First Diameter From Head:

Between 0.115 inches and 0.125 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.270 inches and 0.290 inches

Point Style:

Flat

Internal Drive Style:

Slot

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 203ez or steel comp 303 or steel comp 303 plus x or steel comp 303cu or steel comp 303ma or steel comp 303pb or steel comp 303se or steel comp 416 or steel comp 416 plus x or steel comp 416se or steel comp 430f or steel comp 430fse

Material Specification:

Mil-w-52263 military specification all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-w-52263 spec.