NSN 5305-01-290-8885

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-290-8885 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.170 inches **Fastener Length:** 0.500 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.310 inches **Head Height:** 0.280 inches **First Diameter From Head:** Between 0.068 inches and 0.072 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.330 inches **Point Style:** Flat **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Criticality Code Justification: Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a581 assn standard single material response **Surface Treatment: Passivate Special Test Features:** Special quality control testing

Test Data Document:

Surface Treatment Specification:

M.I.5-28 cagec 94271 mfr ref single treatment response

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5305-01-290-8885

Thread Series Designator:

A003b0

Externally Relieved Body Screw - Page 2 of 2



Unc
Reference Number Differentiating Characteristics:
As differentiated by material which must conform to ships parts control center special quality control provisions and certified free from
mercury contamination
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: