

View Online at <https://aerobasegroup.com/nsn/5305-01-291-0144>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.357 inches

**Fastener Length:**

Between 0.407 inches and 0.438 inches

**Head Style:**

Binding

**Head Diameter:**

Between 0.223 inches and 0.235 inches

**Head Height:**

Between 0.056 inches and 0.063 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Screw Material:**

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

**Screw Material Specification:**

Qq-s-763 federal specification all material responses

**Screw Surface Treatment:**

Passivate

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0