NSN 5305-01-291-5680

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-291-5680 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.282 inches and 0.375 inches **Fastener Length:** Between 0.344 inches and 0.375 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Locking Feature:** Strip threads or patch threads or pellet threads **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c fastener and 40.0 rockwell c fastener Surface Finish: 32.0 microinches threads Material: Steel comp 4140 fastener or steel comp 4340 fastener or steel comp 8740 fastener **Surface Treatment:** Cadmium fastener and chromate fastener **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response fastener **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1190 professional/industrial association standard Shelf Life:

N/a **Unit Of Measure:**

NSN 5305-01-291-5680

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0