## NSN 5305-01-291-6613

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-291-6613

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.345 inches and 0.395 inches
Fastener Length:
Between 0.855 inches and 0.885 inches
Head Style:
Pan
Head Diameter:
Between 0.473 inches and 0.492 inches
Head Height:
Between 0.162 inches and 0.175 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.250 inches
Grip Length:
Between 0.490 inches and 0.510 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Material:
Steel comp e4340 or steel comp 8740
Material Specification:
Mil-s-6049 military specification 1st material response or ams 6322 assn standard 2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas7704 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-01-291-6613

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.