## NSN 5305-01-291-9069



Machine Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-291-9069 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.196 inches and 1.320 inches **Fastener Length:** Between 1.313 inches and 1.375 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.200 inches and 0.225 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303 plus x or steel comp 303se or steel comp 303cu or steel comp 303ma or steel comp 304 or steel comp 304l or steel comp 384 **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 3 type and 2c style Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

Fiig:

A500d0