NSN 5305-01-292-2468

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-292-2468 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.363 inches **Fastener Length:** 1.413 inches **Head Style:** Headless (setscrew) **Shoulder Diameter:** 0.1885 inches first shoulder and 0.1895 inches first shoulder **Shoulder Length:** 0.400 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.188 inches and 0.195 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Shoulder Shape:** Round first shoulder Material: Steel comp e4340 **Material Specification:** Mil-s-5000 military specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837 type 2 cl 2 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Ma e:

Unit Of Measure
Demilitarization:
No

NSN 5305-01-292-2468

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.