## NSN 5305-01-292-5325

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-292-5325 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.620 inches and 0.687 inches **Fastener Length:** Between 0.656 inches and 0.687 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.136 inches and 0.140 inches **Head Height:** Between 0.044 inches and 0.053 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Steel comp 4140 or steel comp e4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1101 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig: A500d0

No

## NSN 5305-01-292-5325

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5626 spec.