NSN 5305-01-292-6304

Fiig: A003b0

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-292-6304 **Thread Class:** 2b **Thread Direction:** Right-hand Thread Length: Between 0.359 inches and 0.391 inches **Fastener Length:** 1.375 inches **Head Style:** Fillister **Head Diameter:** Between 0.433 inches and 0.443 inches **Head Height:** Between 0.234 inches and 0.266 inches **First Diameter From Head:** Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.986 inches and 1.016 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Stainless steel **Material Specification:** Mil-w-52263 military specification single material response or astm a581-75 assn standard single material response or ams5762 assn standard single material response **Surface Treatment:** Oxide film **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

NSN 5305-01-292-6304

Externally Relieved Body Screw - Page 2 of 2



Mil-std (military Standard):

Mil-w-52263 spec.