

View Online at <https://aerobasegroup.com/nsn/5305-01-292-6305>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.169 inches

Fastener Length:

Between 0.219 inches and 0.250 inches

Head Style:

Binding

Head Diameter:

Between 0.223 inches and 0.235 inches

Head Height:

Between 0.056 inches and 0.063 inches

Internal Drive Style:

Slot

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

125000 pounds per square inch

Screw Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Screw Material Specification:

Qq-s-763 federal specification all material responses

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-f-13924 military specification single treatment response

Color:

Black

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-f-13924 spec.