

View Online at <https://aerobasegroup.com/nsn/5305-01-292-6306>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.407 inches and 0.500 inches

Fastener Length:

Between 0.469 inches and 0.500 inches

Head Style:

Pan

Head Diameter:

Between 0.306 inches and 0.322 inches

Head Height:

Between 0.105 inches and 0.115 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

60000 pounds per square inch

Screw Material:

Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1116 or steel comp 1117 or steel comp 1118 or steel comp 1119 or steel comp 1120 or steel comp 1132

Screw Surface Treatment:

Zinc and chromate

Screw Surface Treatment Specification:

Astm b633 type 2 assn standard single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

3 type and 9c style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0