NSN 5305-01-292-6316

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-292-6316

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.378 inches and 0.428 inches
Fastener Length:
Between 0.513 inches and 0.543 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.464 inches and 0.507 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Internal Drive Style:
Torque-set ribbed
Thread Diameter:
0.250 inches
Grip Length:
Between 0.115 inches and 0.135 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard all material responses or ams 4967 assn standard all material responses
Thread Series Designator:
Unjf
Specification Data:
80205-nas1580 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

NSN 5305-01-292-6316

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0