## NSN 5305-01-292-8354

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-292-8354 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.115 inches **Fastener Length:** 0.438 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.143 inches and 0.172 inches **Locking Feature:** Patch threads **First Diameter From Head:** 0.055 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.250 inches **Point Style:** Flat **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 **Countersink Angle:** 100.0 degrees **Externally Relieved Body Diameter Quantity:** 1 Color: Black Material: Steel comp 321 **Material Specification:** Qq-s-763 cl 8 ty a federal specification single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 cl 4 military specification single treatment response

Unc

**Thread Series Designator:** 

## NSN 5305-01-292-8354

Externally Relieved Body Screw - Page 2 of 2



| Shelf Life:       |
|-------------------|
| N/a               |
| Unit Of Measure:  |
|                   |
| Demilitarization: |
| No                |
| Fiig:             |
| riig.             |

Mil-std (military Standard):

Mil-c-13924 spec.