

View Online at <https://aerobasegroup.com/nsn/5305-01-293-5314>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.590 inches and 1.750 inches

Fastener Length:

Between 1.690 inches and 1.750 inches

Head Style:

Pan

Head Diameter:

Between 0.473 inches and 0.492 inches

Head Height:

Between 0.162 inches and 0.175 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

20

Screw Material:

Steel comp 1008 or steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1025 or steel comp 1030 or steel comp 1035 or steel comp 1040 or steel comp 1045 or steel comp 1050 or steel comp 1095 or steel comp 1213 or steel comp 1115 or steel comp 1117 or steel comp 1118 or steel comp 1137 or steel comp 1141 or steel comp 1144 or steel comp 1151 or steel comp 12114 or steel comp 1211 or steel comp 1212 or steel comp 1548 or steel comp 1215 or steel comp 1330

Screw Material Specification:

Astm a108 assn standard all material responses

Screw Surface Treatment:

Zinc and chromate

Screw Surface Treatment Specification:

Astm b633 type 2 cl fe/zn 13 assn standard single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

3 type or 9c style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0