
NSN 5305-01-293-6118

Close Tolerance Screw - Page 1 of 2

3a

28





Thread Class: Thread Direction: Right-hand Thread Length: Between 0.372 inches and 0.422 inches Fastener Length: Between 1.007 inches and 1.037 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.350 inches and 0.399 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.250 inches Grip Length: Between 0.615 inches and 0.635 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads **Product Name:** Navy special project Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment:** Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5305-01-293-6118

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

