## NSN 5305-01-293-6642

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-293-6642



**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.407 inches and 0.500 inches Fastener Length: Between 0.469 inches and 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.306 inches and 0.313 inches **Head Height:** Between 0.103 inches and 0.118 inches Hole Diameter: 0.038 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.190 inches **Hole Quantity:** 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams5737 assn standard single material response **Screw Surface Treatment:** Passivate **Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response Head Hole Configuration Style: Round **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1101 professional/industrial association standard Shelf Life:

N/a

## NSN 5305-01-293-6642

Machine Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A500d0

