# NSN 5305-01-293-9533

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-293-9533



# 3a Thread Direction: Right-hand Thread Length:

**Thread Class:** 

Between 0.202 inches and 0.295 inches

#### Fastener Length:

Between 0.344 inches and 0.375 inches

#### Head Style:

Flat countersunk

#### Head Diameter:

Between 0.371 inches and 0.385 inches

#### Internal Drive Style:

Torque-set ribbed

#### **Thread Diameter:**

0.190 inches

#### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Countersink Angle:

Between 99.0 degrees and 101.0 degrees

#### **Product Name:**

Navy special project

#### Screw Material:

Iron alloy 660

#### Screw Material Specification:

Ams5737 assn standard single material response

#### Screw Surface Treatment:

Passivate

# Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjf

## **Specification Data:**

80205-nas1102 professional/industrial association standard

#### Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5305-01-293-9533

Machine Screw - Page 2 of 2

Fiig: A500d0

