NSN 5305-01-293-9550

Panel Screw Assembly - Page 1 of 1

No Fiig: A003b0



View Online at https://aerobasegroup.com/nsn/5305-01-293-9550 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.420 inches and 0.500 inches **Fastener Length:** Between 0.470 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Special Features:** Dflat washer 0.215 od x 0.120 id x 0.009 in. Mim, 0.012 in maximum thk; bushing 0.137 in min, 0.143 in max.Dia; in 0.172 in.Dia hole; split lockwasher 0.212 od x 0.115 id x 0.017 in min, 0.033 in maximum thk; Material: Steel comp 303 secondary washer **Material Specification:** Qq-b-626 federal specification single material response stand-off **Surface Treatment:** Passivate secondary washer **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response secondary washer **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**