NSN 5305-01-294-3037

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-294-3037

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.345 inches and 0.438 inches	
Fastener Length:	
Between 0.407 inches and 0.438 inches	
Head Style:	
Pan no. 2	
Head Diameter:	
Between 0.306 inches and 0.313 inches	
Head Height:	
Between 0.103 inches and 0.118 inches	
Locking Feature:	
Patch threads	
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.190 inches	
Thready Qty Per Inch (tpi):	
32	
Min. Tensile Strength (psi):	
160000 pounds per square inch	
Surface Finish:	
32.0 microinches threads	
Material:	
Steel comp 4140 fastener or steel comp e4340 fastener or steel comp 8740 fastener	
Material Specification:	
Mil-s-5626 military specification 1st material response fastener or mil-s-5000 military specification 2nd material response fastener or	
mil-s-6049 military specification 3rd material response fastener	
Surface Treatment:	
Cadmium fastener and chromate fastener	
Surface Treatment Specification:	
Qq-p-416 ty2 cl2 federal specification single treatment response fastener	
Thread Series Designator:	
Unjf	
Specification Data:	
80205-nas1191 professional/industrial association standard	
Shelf Life:	
N/a	
Unit Of Measure:	

-

NSN 5305-01-294-3037

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.