Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-294-6803



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.789 inches and 0.875 inches Fastener Length: Between 0.845 inches and 0.875 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.262 inches and 0.270 inches **Head Height:** Between 0.159 inches and 0.164 inches Hole Diameter: Between 0.033 inches and 0.039 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Hole Quantity: 6 Hole Type: Drilled Thready Qty Per Inch (tpi): 36 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Hole Configuration Style: Round internal hexagon Material: Steel Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:**

Unrf

NSN 5305-01-294-6803

Socket Head Cap Screw - Page 2 of 2



Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0